

## Scan Spray Lab XL / 500ml

Version number: GHS 1.0

Date of compilation: 2016-01-19

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

**1.1 Product identifier**

Trade name **Scan Spray Lab XL / 500ml**  
 Registration number (REACH) not relevant (mixture)

**Other means of identification**

**Article number** 400040

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses coating for particular industrial and professional uses

**1.3 Details of the supplier of the safety data sheet**

Dentaco GmbH & Co. KG  
 Max - Keith - Straße 46  
 45136 Essen  
 Germany

Telephone: + 49 201 / 80 98 29 0  
 Telefax: + 49 201 / 80 98 29 99  
 e-mail: info@dentaco.de  
 Website: www.dentaco.de

**1.4 Emergency telephone number**

Emergency information service This number is only available during the following of-  
 fice hours: Mon-Fri 09:00 - 17:00

### SECTION 2: Hazards identification

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 (CLP)**

Section	Hazard class	Cat-egory	Hazard class and category	Hazard state-ment
2.3	aerosols	Cat. 1	(Aerosol 1)	H222,H229
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	Cat. 3	(STOT SE 3)	H336
4.1C	hazardous to the aquatic environment - chronic hazard	Cat. 3	(Aquatic Chronic 3)	H412

**Remarks**

For full text of H-phrases: see SECTION 16.

**Supplemental hazard information**

Code	Supplemental hazard information
EUH066	repeated exposure may cause skin dryness or cracking

**The most important adverse physicochemical, human health and environmental effects**

Spillage and fire water can cause pollution of watercourses.

## Scan Spray Lab XL / 500ml

Version number: GHS 1.0

Date of compilation: 2016-01-19

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008 (CLP)****Signal word****Danger****Pictograms**

GHS02, GHS07

**Hazard statements**

H222 Extremely flammable aerosol.  
H229 Pressurized container: may burst if heated.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements****Precautionary statements - general**

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read label before use.

**Precautionary statements - prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

**Precautionary statements - response**

P312 Call a POISON CENTER/doctor if you feel unwell.

**Precautionary statements - storage**

P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

**Precautionary statements - disposal**

P501 Dispose of contents/container to industrial combustion plant.

**Additional labelling requirements**

EUH066 Repeated exposure may cause skin dryness or cracking.

**Hazardous ingredients for labelling:** pentane

**2.3 Other hazards**

Repeated exposure may cause skin dryness or cracking.

## Scan Spray Lab XL / 500ml






Version number: GHS 1.0

Date of compilation: 2016-01-19

**SECTION 3: Composition/information on ingredients****3.1 Substances**

not relevant (mixture)

**3.2 Mixtures****Description of the mixture**

Name of substance	Identifier	wt%	Classification acc. to 1272/2008/EC	Pictograms
butane	CAS No 106-97-8  EC No 203-448-7	50 - < 75	Flam. Gas 1 / H220 Press. Gas L / H280	
propane	CAS No 74-98-6  EC No 200-827-9	10 - < 25	Flam. Gas 1 / H220 Press. Gas L / H280	
pentane	CAS No 109-66-0  EC No 203-692-4	10 - < 25	Flam. Liq. 1 / H224 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	
isobutane	CAS No 75-28-5  EC No 200-857-2	1 - < 5	Flam. Gas 1 / H220 Press. Gas C / H280	
ethanol	CAS No 64-17-5  EC No 200-578-6	1 - < 5	Flam. Liq. 2 / H225	

For full text of abbreviations: see SECTION 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures****General notes**

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

**Following inhalation**

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

**Following skin contact**

Wash with plenty of soap and water.

**Following eye contact**

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

## Scan Spray Lab XL / 500ml

Version number: GHS 1.0

Date of compilation: 2016-01-19

**Following ingestion**

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

**4.2 Most important symptoms and effects, both acute and delayed**

Narcotic effects.

**4.3 Indication of any immediate medical attention and special treatment needed**

none

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing media**

water spray, alcohol resistant foam, BC-powder

**Unsuitable extinguishing media**

water jet

**5.2 Special hazards arising from the substance or mixture****Hazardous combustion products**nitrogen oxides (NO<sub>x</sub>), carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>)**5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Remove persons to safety.

**For emergency responders**

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

**6.2 Environmental precautions**

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose it.

**6.3 Methods and material for containment and cleaning up****Advices on how to contain a spill**

Covering of drains.

**Other information relating to spills and releases**

Place in appropriate containers for disposal. Ventilate affected area.

**6.4 Reference to other sections**

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## Scan Spray Lab XL / 500ml

Version number: GHS 1.0

Date of compilation: 2016-01-19

**SECTION 7: Handling and storage****7.1 Precautions for safe handling****Recommendations****• Measures to prevent fire as well as aerosol and dust generation**

Use local and general ventilation. Use only in well-ventilated areas.

**Advice on general occupational hygiene**

Wash hands after use. Do not to eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

**7.2 Conditions for safe storage, including any incompatibilities****Managing of associated risks****• Flammability hazards**

Do not spray on an open flame or other ignition source. Protect from sunlight.

**Incompatible substances or mixtures**

Observe hints for combined storage.

**Consideration of other advice****• Packaging compatibilities**

Only packagings which are approved (e.g. acc. to ADR) may be used.

**7.3 Specific end use(s)**

See section 16 for a general overview.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****National limit values****Occupational exposure limit values (Workplace Exposure Limits)**

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Source
EU	n-pentane	109-66-0	IOELV	1,000	3,000			2006/15/EC
EU	ethyl methyl ketone	78-93-3	IOELV	200	600	300	900	2000/39/EC
GB	butane	106-97-8	WEL	600	1,450	750	1,810	EH40/2005
GB	pentane	109-66-0	WEL	600	1,800			EH40/2005
GB	titanium dioxide	13463-67-7	WEL		10			EH40/2005
GB	titanium dioxide	13463-67-7	WEL		4			EH40/2005
GB	ethanol	64-17-5	WEL	1,000	1,920			EH40/2005
GB	silica, amorphous	7631-86-9	WEL		6			EH40/2005
GB	silica, amorphous	7631-86-9	WEL		2.4			EH40/2005
GB	butan-2-one (methyl ethyl ketone)	78-93-3	WEL	200	600	300	899	EH40/2005

**Notation**

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average

## Scan Spray Lab XL / 500ml

Version number: GHS 1.0

Date of compilation: 2016-01-19

**Relevant DNELs/DMELs/PNECs and other threshold levels****• relevant DNELs of components of the mixture**

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
pentane	109-66-0	DNEL	432 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
pentane	109-66-0	DNEL	3,000 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
ethanol	64-17-5	DNEL	1,900 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
ethanol	64-17-5	DNEL	343 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
ethanol	64-17-5	DNEL	950 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects

**• relevant PNECs of components of the mixture**

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
pentane	109-66-0	PNEC	3,600 µg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
pentane	109-66-0	PNEC	880 µg/l	aquatic organisms	water	continuous
ethanol	64-17-5	PNEC	580 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
ethanol	64-17-5	PNEC	2.75 mg/l	aquatic organisms	water	continuous

**8.2 Exposure controls****Appropriate engineering controls**

General ventilation.

**Individual protection measures (personal protective equipment)**

Personal protective equipment shall be used when the risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

**Eye/face protection**

Wear eye/face protection.

**Skin protection****• hand protection**

Wear protective gloves.

**• other protection measures**

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

**Respiratory protection**

During spraying wear suitable respiratory equipment.

## Scan Spray Lab XL / 500ml

Version number: GHS 1.0

Date of compilation: 2016-01-19

**Environmental exposure controls**

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****Appearance**

Physical state	aerosol (spray aerosol)
Colour	white
Odour	characteristic

**Other physical and chemical parameters**

pH (value)	
Melting point/freezing point	not determined
Initial boiling point and boiling range	-161.5 °C at 1,013 hPa
Flash point	-40 °C
Evaporation rate	not determined
Flammability (solid, gas)	Flammable aerosol in accordance with GHS criteria
Explosive limits	
• lower explosion limit (LEL)	1.4 vol%
• upper explosion limit (UEL)	15 vol%
Vapour pressure	2,700 Pa
Density	0.67 - 0.69 g/cm <sup>3</sup> at 20 °C
Solubility(ies)	not determined
Partition coefficient	
n-octanol/water (log KOW)	This information is not available.
Auto-ignition temperature	260 °C
Viscosity	not relevant (aerosol)
Explosive properties	none
Oxidising properties	none

**9.2 Other information**

Solvent content	13.52 %
Solid content	2.05 %
propellant content	84.43 %

**SECTION 10: Stability and reactivity****10.1 Reactivity**

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s): risk of ignition

**10.2 Chemical stability**

See below "Conditions to avoid".

**10.3 Possibility of hazardous reactions**

No known hazardous reactions.

**Scan Spray Lab XL / 500ml**

Version number: GHS 1.0

Date of compilation: 2016-01-19

**10.4 Conditions to avoid**

Do not spray on an open flame or other ignition source. - Keep away from heat.

**Hints to prevent fire or explosion**

Protect from sunlight.

**Physical stresses which might result in a hazardous situation and have to be avoided**

strong shocks

**10.5 Incompatible materials**

There is no additional information.

**10.6 Hazardous decomposition products**

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

**SECTION 11: Toxicological information****11.1 Information on toxicological effects**

Test data are not available for the complete mixture.

**Classification procedure**

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**Classification according to GHS (1272/2008/EC, CLP)****Acute toxicity**

Shall not be classified as acutely toxic.

**Skin corrosion/irritation**

Shall not be classified as corrosive/irritant to skin.

**Serious eye damage/eye irritation**

Shall not be classified as seriously damaging to the eye or eye irritant.

**Respiratory or skin sensitisation**

Shall not be classified as a respiratory or skin sensitiser.

**Summary of evaluation of the CMR properties**

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

**Specific target organ toxicity (STOT)****• Specific target organ toxicity - single exposure**

May cause drowsiness or dizziness.

**• Specific target organ toxicity - repeated exposure**

Shall not be classified as a specific target organ toxicant (repeated exposure).

**Aspiration hazard**

Shall not be classified as presenting an aspiration hazard.

**Other information**

Repeated exposure may cause skin dryness or cracking.



## Scan Spray Lab XL / 500ml

Version number: GHS 1.0

Date of compilation: 2016-01-19

### SECTION 12: Ecological information

#### 12.1 Toxicity

Harmful to aquatic life with long lasting effects.

##### Aquatic toxicity (acute)

##### Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
butane	106-97-8	LC50	27.98 mg/l	fish	96 hours
butane	106-97-8	EC50	7.71 mg/l	algae	96 hours
propane	74-98-6	LC50	27.98 mg/l	fish	96 hours
propane	74-98-6	EC50	7.71 mg/l	algae	96 hours
pentane	109-66-0	LL50	27.55 mg/l	fish	96 hours
pentane	109-66-0	EL50	48.11 mg/l	aquatic invertebrates	48 hours
pentane	109-66-0	EC50	2.8 mg/l	aquatic invertebrates	48 hours
ethanol	64-17-5	LC50	14.2 g/l	fish	96 hours
ethanol	64-17-5	EC50	12.9 g/l	fish	96 hours

##### Aquatic toxicity (chronic)

May cause long-term adverse effects in the aquatic environment.

##### Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
ethanol	64-17-5	LC50	>0.08 mg/l	fish	42 d
ethanol	64-17-5	EC50	22.6 g/l	algae	10 d
ethanol	64-17-5	ErC50	675 mg/l	algae	4 d

##### Biodegradation

The relevant substances of the mixture are readily biodegradable.

#### 12.2 Persistence and degradability

Data are not available.

##### Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time
pentane	109-66-0	oxygen depletion	3 %	7 d
ethanol	64-17-5	oxygen depletion	74 %	5 d

#### 12.3 Bioaccumulative potential

Data are not available.

## Scan Spray Lab XL / 500ml

Version number: GHS 1.0

Date of compilation: 2016-01-19

**Bioaccumulative potential of components of the mixture**

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
butane	106-97-8		1.09	
propane	74-98-6		1.09	
pentane	109-66-0	171	3.45	
ethanol	64-17-5		-0.35	

**12.4 Mobility in soil**

Data are not available.

**12.5 Results of PBT and vPvB assessment**

Data are not available.

**12.6 Other adverse effects**

Data are not available.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Sewage disposal-relevant information**

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

**Waste treatment of containers/packagings**

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

**Remarks**

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

**SECTION 14: Transport information**

- 14.1** UN number **1950**
- 14.2** UN proper shipping name **AEROSOLS**
- 14.3** Transport hazard class(es)  
Class 2 (gases) (aerosol)  
Subsidiary risk(s) 2.1 (flammability)
- 14.4** Packing group not assigned to a packing group
- 14.5** Environmental hazards none (non-environmentally hazardous acc. to the dangerous goods regulations)
- 14.6** Special precautions for user  
Provisions for dangerous goods (ADR) should be complied within the premises.
- 14.7** Transport in bulk according to Annex II of MARPOL and the IBC Code  
The cargo is not intended to be carried in bulk.

**Information for each of the UN Model Regulations****• Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)**

UN number	1950
Proper shipping name	AEROSOLS
Class	2
Classification code	5F
Danger label(s)	2.1

## Scan Spray Lab XL / 500ml

Version number: GHS 1.0

Date of compilation: 2016-01-19



Special provisions (SP)	190, 327, 344, 625
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D
<b>• International Maritime Dangerous Goods Code (IMDG)</b>	
UN number	1950
Proper shipping name	AEROSOLS
Class	2.1
Danger label(s)	2.1



Special provisions (SP)	63, 190, 277, 327, 344, 959
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
EmS	F-D, S-U
<b>• International Civil Aviation Organization (ICAO-IATA/DGR)</b>	
UN number	1950
Proper shipping name	Aerosols, flammable
Class	2.1
Danger label(s)	2.1



Special provisions (SP)	A145, A167
Excepted quantities (EQ)	E0
Limited quantities (LQ)	30 kg

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
**Relevant provisions of the European Union (EU)****• Directive 75/324/EEC relating to aerosol dispensers****Classification of the gas/aerosol** Extremely flammable**Labelling**

Pressurized container: may burst if heated  
 Keep out of the reach of children  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
 Do not pierce or burn, even after use  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C

**15.2 Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

## Scan Spray Lab XL / 500ml

Version number: GHS 1.0

Date of compilation: 2016-01-19

### SECTION 16: Other information

#### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2000/39/EC	Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Chronic	hazardous to the aquatic environment - chronic hazard
Asp. Tox.	aspiration hazard
BCF	BioConcentration Factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
COD	chemical oxygen demand
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits, Table 1: List of approved workplace exposure limits ( <a href="http://www.nationalarchives.gov.uk/doc/open-government-licence/">http://www.nationalarchives.gov.uk/doc/open-government-licence/</a> )
EmS	Emergency Schedule
Flam. Gas	flammable gas
Flam. Liq.	flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
IOELV	indicative occupational exposure limit value
log KOW	n-octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	parts per million
Press. Gas	gas under pressure
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
STEL	short-term exposure limit

## Scan Spray Lab XL / 500ml

Version number: GHS 1.0

Date of compilation: 2016-01-19

Abbr.	Descriptions of used abbreviations
STOT SE	specific target organ toxicity - single exposure
TWA	time-weighted average
vPvB	very Persistent and very Bioaccumulative
WEL	workplace exposure limit

### Key literature references and sources for data

- Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU
- Regulation (EC) No. 1272/2008 (CLP, EU GHS)

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards/environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H220	extremely flammable gas
H222	extremely flammable aerosol
H224	extremely flammable liquid and vapour
H225	highly flammable liquid and vapour
H229	pressurized container: may burst if heated
H280	contains gas under pressure; may explode if heated
H304	may be fatal if swallowed and enters airways
H336	may cause drowsiness or dizziness
H411	toxic to aquatic life with long lasting effects
H412	harmful to aquatic life with long lasting effects

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.